



\*If "Shift mode" is selected in the "Disp mode" menu, the display will toggle between time, weekday, date, internal temperature, external temperature (if enabled), humidity (if enabled), pressure (if enabled), weather (if enabled) and weather trend (if enabled) according to the selected order in the "Disp order" menu. The standby screen (only one single led on at lowest brightness or all leds off) can only be selected via the remote. The default toggle interval is approx. 10 seconds when the clock is shown and approx. 5 seconds when the weekday, date, internal temperature, external temperature, humidity, pressure, weather and weather trend are shown.

The weather display can show up to five different kinds of weather types:

- Two arrows up: Unstable (dPTdT > 250 Pa/h)
- One arrow up: Good (50 Pa/h < dPTdT < 250 Pa/h)
- A vertical line: Stable (50 Pa/h < dPTdT < 50 Pa/h)
- One arrow down: Rainy (> 250 Pa/h < dPTdT < -50 Pa/h)
- Two arrows down: Stormy (dPTdT < -250 Pa/h)

During the first half four after power has been turned on the weather display will show "No weather" and the trend display will show "No trend".

On the trend display the current weather type will be shown on position 10 on the display. The previous weather type will be shown on position 9 on the display an so on down to position 1 on the display.

The first time the led watch is powered on (or after a reset), it will go directly into the "Remote" menu, where you learn it all the remote IR codes. After this it guides you through the menus "Set time", "Set date", "Set format" and "Daylight". When you have set the time, date, weekday, date format and daylight mode it will enter the "Operation" menu.

The led watch has four optional buttons: Plus, Minus, Enter and Menu (It is not nesseeary to connect buttons to the led watch). The led watch is designed to be used together with an Apple IR remote, where it uses four remote buttons: Up, Down, Center and Menu. The led watch can be operated entirely by the remote.

The led watch has been designed to automatically adjust the time when the day light saving period changes. It will only do this in the "Operation" menu.

The brightness level can be adjusted from 0 to 15. The selected brightness level is stored in the eeprom, so the led watch remembers the brightness level when the power is switched off.

If nesseeary it is possible to reset all the settings (time, weekday, date, date format, day light saving zone, temperature unit, pressure unit, display mode, display order, display time, standby led, brightness, remote, external temperature sensor and add on pcb) by holding the menu button down while switching power on or in the the "Reset all" menu.

This menu is used to select in which the order the different display are shown in the "Operation" menu. Changing the display order is done by swapping displays. Eg. selecting Date as display number 1 will set Time as display number 3.

Displays selected after the Standby display will not be visible in the "Operation" menu. Eg. if display 1 is Time, display 2 is Weekday and display 3 is Standby only Time and Weekday will be shown in the "Operation" menu.

Selecting Standby as display number 1 will reset to default display order.

The displays shown in the "Disp order" menu depends on if the ext temp has been enabled and/or if the "Add on pcb" has been enabled. The are 4 scenarios:

Ext temp disabled and add on pcb disabled. Default display order is:

- 1: Time
- 2: Weekday
- 3: Date
- 4: Int temp
- 5: Ext temp
- 6: Standby

Ext temp disabled and add on pcb enabled. Default display order is:

- 1: Time
- 2: Weekday
- 3: Date
- 4: Int temp
- 5: Humidity
- 6: Pressure
- 7: Weather
- 8: Trend
- 9: Standby

Ext temp enabled and add on pcb disabled. Default display order is:

- 1: Time
- 2: Weekday
- 3: Date
- 4: Int temp
- 5: Ext temp
- 6: Humidity
- 7: Pressure
- 8: Weather
- 9: Trend
- 10: Standby

Ext temp enabled and add on pcb enabled. Default display order is:

- 1: Time
- 2: Weekday
- 3: Date
- 4: Int temp
- 5: Ext temp
- 6: Humidity
- 7: Pressure
- 8: Weather
- 9: Trend
- 10: Standby

The example above shows how the display time is adjusted if both the ext temp and the add on pcb are enabled and the display order hasn't been changed. The example shows the default display time for all of the displays 01:00. It is possible to select a display time between 1 sec and 60 sec.

If the Standby display has been selected as display number eg. five, it will only be possible to adjust the display time for the first four displays 01:00. When pressing the enter/center button after display four it will return to the main menu.